

Superhawk

**2000kg
UNDERLIFT**



2000kg Underlift



CONVERSIONS

Tel: 01264 332919

Fax: 01264 334125 E-mail: info@jjconversions.co.uk Web site: www.jjconversions.co.uk
Excellent Finance Packages available. Part Exchange is welcome.

Superhawk

SPECIFICATIONS



New Superhawk 2000kg Underlift

Twin hydraulic lift rams, hydraulic boom extension, hydraulic load levelling, directional winch sheaf, open ended swivel frame with 4 Spacer Bars, sliding ratchets and 'Y' type tensioning straps, electro-hydraulic power unit with full remote control handset.

Superhawk Module Body

- Front through locker,
- Full length lockers on offside & nearside,
- Louvre ventilation panels in lockers,
- Contoured rear panel,
- 2 Free-standing GRP beacon mounts,
- Aluminium tread plate floor,
- Stainless steel hinges & door locks with rubber gaskets,
- All doors operating on gas struts,
- Interior lights in each locker,
- Stainless steel protection strips in bottom edge of locker doors,
- Black plastic coated hand rail,
- Galvanised step fitted to rear panel,
- Galvanised subframe to manufacturers guidelines,
- 2 Ton electric winch,
- Electrical installation including lightbar, repeater lights, loading lights, rear lights, locker lights, 7 pin socket, switch panel and printed circuit board inc. relays,
- 70" Lightbar with 4 rotators & repeater lights,
- 2 x Work lamps fitted to rear of lockers,
- 2 x Work lamps fitted in rear panel,
- Emergency stop & reset system,
- Towing attachment with 50mm ball & pin zinc passivated,
- Paintwork in ICI two pack (to match cab), oven baked, waxoiled on underside of body.
- **Accessory Kit:** 3 Fuel cans, 1 water container, first aid kit, fire extinguisher, angle headed torch, 1 pair of gloves, trailer board.
- **Wreckers Kit:** Shovel, crow bar, lever bar, sledge hammer, safety helmet, broom, 6 road cones fitted in zinc passivated brackets.
- **Options:**
There are various options available including hydraulic crane jib, stainless steel body system with 5 year warranty, along with numerous others, please ask for details.

Suitable for chassis from 5 – 7.5 ton GVW

The capacity of the equipment may not be the same as the capacity of the completed vehicle, due to chassis variations. All equipment supplied with the vehicle are subject to our normal conditions of sale. All equipment designs may vary from those illustrated in this literature and the company reserves the right to change these details at will.



Tel: 01264 332919

Fax: 01264 334125 E-mail: info@jjconversions.co.uk

Web site: www.jjconversions.co.uk